

800 Series Compact Transmitters

The 800 Series Transmitters are rugged, compact, loop-powered instruments that are ideally suited for hazardous locations and hostile environments where space is limited. They offer a true pressure switch replacement and come with industry standard outputs to meet applications where low-cost, discrete, and continuous monitoring is required or preferred.

	805PT		805QS		815PT	815DT	815LT
	C	V	C	V			
4-20mA Output	●		●		●	●	●
1-5 VDC (low power) Output		●		●	●	●	●
Solid-State Switch Output			●	●	●	●	●
HART Protocol					●	●	●
Modbus RTU Protocol					●	●	●
External Zero/Span Points					●	●	●
Submersible for Level Measurement							●
Pressure Ranges	0-5 psi 0-15 psi 0-50 psi	0-138 in. wc. to 0-30,000 psi	0-138 in w.c. to 0-500 psid	0-35 ft. w.c. to 0-575 ft. w.c.			
Response Time	5ms				<=70ms	<=70ms	<=70ms
Accuracy	± 0.25% URL				± 0.25%	± 0.25%	± 0.25%
Construction	316SS Housing (CF8M)						
Standard Process Connection	1/2" NPT(M) with 1/4" NPT(F)					1/4" NPT(F) (Hi & Lo side)	1/2" NPT(M) with 1/4" NPT(F) with removable PVC nose cone



- Explosion-proof housing that is NEMA 4X and IP66 rated (815LT IP68)
- Local Indicating Display option available
- Hermetically sealed leads
- FM, ATEX, IECEx, and INMETRO certified for hazardous locations in U.S., Canada, and Europe
- CRN approved
- NACE option available
- Dual Seal approval option available
- Absolute Pressure range options
- 3 Year Warranty

SORInc.com

Engineered to Order with Off-the-Shelf Speed